

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2005-252783

(43)Date of publication of application : 15.09.2005

(51)Int.Cl.

H04B 10/04
H01S 5/068
H04B 10/02
H04B 10/06
H04B 10/14
H04B 10/18
H04B 10/26
H04B 10/28

(21)Application number : 2004-062089

(71)Applicant : MITSUBISHI ELECTRIC CORP

(22)Date of filing : 05.03.2004


(72)Inventor : YAMADA KAZUYOSHI
ARIGA HIROSHI

(54) OPTICAL TRANSMITTER

(57)Abstract:

PROBLEM TO BE SOLVED: To secure a predetermined eye mask margin in an optical transmitter without depending on a transmission speed.

SOLUTION: The optical transmitter includes a semiconductor laser drive circuit 1, and a semiconductor laser 4 for generating and outputting modulated laser light based on the modulation current of the semiconductor laser drive circuit 1. In the above optical transmitter, a phase difference adjustment circuit 2 is provided in the pre-stage of the semiconductor laser drive circuit 1, so as to reduce a phase difference produced between data signals. The phase difference adjustment circuit 2 includes an impedance control line 5, a resistor element 7 having a parasitic inductance component (or an inductor having a parasitic resistance component), and a DC cutoff capacitor 8.



*** NOTICES ***

JP0 and INPIT are not responsible for any damages caused by the use of this translation.

- 1.This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.*** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1]

In an optical transmitter provided with a semiconductor laser driving circuit which operates an inputted signal wave form of a data signal orthopedically, and a semiconductor laser which carries out the generation output of the modulated laser light based on a modulated current flow which this semiconductor laser driving circuit outputs,

An optical transmitter equipping the preceding paragraph of said semiconductor laser driving circuit with a phase contrast equalization circuit for reducing phase contrast generated between data signals.

[Claim 2]

Said phase contrast equalization circuit,

The transmission line which transmits said data signal to said semiconductor laser driving circuit,

A series resonant circuit connected to said transmission line,

A preparation,

Said series resonant circuit,

An inductor which has a resistance element which has a parasitic inductance component, or a parasitic resistive component,

A capacitance device,

The optical transmitter according to claim 1 characterized by preparation *****.

[Claim 3]

The optical transmitter according to claim 1 or 2, wherein said series resonant circuit is connected to an input side or an output side of said transmission line.

[Claim 4]

An optical transmitter of any one statement of claim 1-3 which said transmission line is a differential line and is characterized by connecting said phase contrast equalization circuit to each of this differential line.

[Claim 5]

An optical transmitter of any one statement of claim 1-3, wherein said transmission line is a single phase track.

[Claim 6]

An optical transmitter of any one statement of claim 1-5, wherein said transmission line is a micro slip track.

[Translation done.]